



# GOVERNMENT POLYTECHNIC, AURANGABAD

(An autonomous institute of govt. of Maharashtra )  
Near Peer Bazar, 0 Osmanpura Station road, Aurangabad  
Phone: 233/524724 /2321917/2353644 Resi : 2331562  
Website: gpabad.ac.in E-mail:gpaur@rediffmail.com

No.GPA/Store/2017-18/14028

Date:-30/8/2017

## ENQUIRY FOR QUOTATION OF STEEL BOOK CASE.

Sealed Quotations are invited for the supply of above mentioned Furniture Items as described under **due on 07.09.2017** subject to the given terms and conditions.

Sr. No.	Name of Materials with Specification	Quantity Required
1	<b><u>STEEL BOOK CASE</u></b> <ul style="list-style-type: none"><li>• <b><u>Over All Size</u></b> : The overall size of the Book case should be 2500mm (H) x 915mm (W) x 305mm (D)</li><li>• <b><u>Shelves</u></b> : The book case should have <b>Six</b> Shelves making Seven Compartments manufactured out of 20 G (1mm) thick sheet.</li></ul>	20 Nos.
2	<b><u>STEEL BOOK CASE</u></b> <ul style="list-style-type: none"><li>• <b><u>Over All Size</u></b> : The overall size of the Book case should be 1675mm (H) x 840mm (W) x 305mm (D)</li><li>• <b><u>Shelves</u></b> : The book case should have <b>Three</b> Shelves making Four Compartments manufactured out of 20 G (1mm) thick sheet.</li></ul>	20 Nos.
	<b>Specification :</b> <ol style="list-style-type: none"><li>1) <b><u>Sides, Top, Back And Bottom</u></b> : The sides top, back and bottom of the Book Case shall be manufactured out of 20 G (1 mm) this MS Sheet</li><li>2) <b><u>Sliding Glass Shutter</u></b> : Each compartment of the Book Case should be provided with shutter manufactured out of 20 G (1mm) MS Sheet with 3mm thick Glass fitted to the shutter fixed with rubber beading having packing screws at the back side of the border of the glass. The shutter should disappear when opened and slide smoothly on the top supports provided for sliding. The shutter should be provided with individual locking arrangement and two chrome plated handles for each shutter. The lock should be provided with keys interchangeable with each other.</li><li>3) <b><u>Colour</u></b> : a) <b>Stoving Enamel Spray Paint</b> : All dents, burns and sharp edges shall be removed from the various components and they shall be scrubbed and rinsed to remove grease rust, scales. All Steel parts shall be given phosphating treatment followed by cost of suitable primer such as zinc chromate red oxide. Putty shall be applied to all surface requiring filling . Then two coats of stove enameled olive green or T.A. grey or any other shade as per choice of consignee shall be applied / painted and backed up to 80 to 120 centigrades. b) <b>Epoxy Polyester Powder Coated</b> : All the metal parts should be coated with "epoxy polyester powder coated of silver gray or "TA" grey or any other shade with as per choice of consignee. All metal parts should be thoroughly in house pre-treated by individual hot deep tank process, including degreasing, picking, phosphating, give phosphate coating conforming to IS 3618-1966 class C. The treated material should be then coated with epoxy polyester powder minimum 50 micron thickness (+ / - 0.5%) and oven backed at 180 to 200 centigrade. All these process must be done in house only. These works cannot be outsourced.</li></ol>	



